



# **Dräger Alcotest® 4000 Alcohol Screening Device**

The breathalyser Dräger Alcotest® 4000 offers responsible drivers a reliable way to test their breath alcohol and gives them the assurance of being legal to drive. This is ensured by precise measurement technology identical to that used by the police: over 30 million breath alcohol tests a year.



#### **Benefits**

#### So that uncertainty doesn't come along for the ride

Have you already had one glass of wine too many or is your blood alcohol content still in the green?

Whether there is still residual alcohol in the body is something that people often find out too late. With the Dräger Alcotest 4000 you can test yourself at any time if you are ready to drive. This way, you can be more relaxed when faced with alcohol checkpoints by police or employer. No residual alcohol, no stress.

#### Fast and reliable alcohol tester

Whether after a business lunch, at a party or the morning after: Thanks of the DrägerSensor you always obtain a precise result when measuring the residual alcohol value. The measurement function is simply activated with the back-lit function button. Optional audible feedback provides additional orientation. The device is ready to use in seconds and the breath test can be performed immediately. The same button is used to navigate through the menu.

#### Replaceable mouthpiece

The mouthpiece is intuitive to fit and protected by a cap. A new mouthpiece should be used for each person being tested. Additional mouthpieces are available as accessories. The air channel passes the exhaled air over the device, and only a small sample of this air is drawn for analysis. This ensures that there is no residual alcohol in the device and that all measurements remain precise and reliable. The same method is also used by the police.

#### Always ready for use

On cool winter nights or a hot summer day: The device is ready for use almost immediately. The temperature range for measurements ranges from -5 °C to +50 °C.

#### Handy and discreet

Thanks to its compact design, the Alcotest 4000 fits into a trouser pocket. Therefore you can take a measurement discreetly at any time – no matter where you are.

#### Designed for years of use

The Alcotest 4000 is Made in Germany and meets the highest quality standards. Regular calibration of the device ensures that the measurement technology will remain precise for a long time. The worldwide, regional Dräger service network ensures that you can keep using the device for many years.

### **Benefits**

#### Precision for over 65 years: the measurement technology used by the police

Dräger has been one of the world market leader and professional supplier of breathalcohol measuring devices for the police and industry for over 65 years. The measurement technology in the Alcotest 4000 is identical with that in devices used for highly precise breath alcohol tests.

Consistent advances in technology over six decades have made the Alcotest 4000 incomparably fast and reliable today. As a private user or professional driver you can simply pre-empt unpleasant surprises if your breath alcohol content (BrAC) is checked.

Over 30 million breath alcohol tests are performed with Dräger instruments around the world each year.

#### Accessories



#### Mouthpieces

Five replacement mouthpieces. Hygienic and individually wrapped.



#### Microfibre pouch

Protects against dust and scratches.

## **Related Products**



#### Dräger DrugCheck® 3000

Use the Dräger DrugCheck® 3000 to find out within minutes if a person recently consumed certain drugs. The compact and quick saliva (oral fluid) based drug test yields reliable results affordably and easily. The non-invasive drug test kit does not require electricity and can therefore be used anywhere.

## Technical Data

Specific   Specific   O to 5.00 %; if the limits of the measuring range are exceeded, a message is displayed   Automatic sampling when minimum volume resp. blow time is reached;   Automatic sampling when minimum volume resp. blow time is reached;   Automatic sampling when end of breath is reached;   depending on configuration   Approx. 4 seconds after switching on   After approx. 3 s (at 0.00 %s);   After approx. 3 s (at 0.00 %s);   After approx. 3 s (at 0.00 %s);   After approx. 10 s (at 1.00 %s, room temperature)   Fo to *50 °C / 23 to 122 °F   For the temperature   Fo to *50 °C / 23 to 122 °F   For the temperature   For the t	Measuring principle	Electrochemical Dräger sensor for 1/4" technology, alcohol
Sampling Automatic sampling when minimum volume resp. blow time is reached; Automatic sampling when end of breath is reached; Automatic sampling when end of breath is reached; depending on configuration  Ready for use Approx. 4 seconds after switching on Display of the measurement results After approx. 10 s (at 1.00 %), room temperature) Operating temperature -5 to +50 °C / 23 to 122 °F Relative humidity 10 to 100 % relative humidity (non-condensing and in operating state)  Ambient pressure 600 to 1,300 hPa / 17.7 to 38.4 inch Hg Display Graphic backlit LCD display; 32 x 22 mm / 1.3" x 0.9" (128 x 64 pixels)  LED Blue light emitting diode (LED) to support the indication of results and warning message  Audible signal Various acoustic signals to support messages and warnings on the display  Datalogger Memory of last 400 tests Power supply Replaceable CR123A-Battery (1.pcs), charge level indicator in display, with one battery up to 1,500 breath tests can be done.  Mouthpiece Hygienically and individually packed Operating concept Measurement functions can be performed using just one button Wet gas or dry gas calibration Housing Impact resistant ABS/PC Dimensions (W x H x D), weight Approx. 50 x 133 x 29 mm / approx. 120 g, incl. Battery Vibration and shock EN 60068-2-32 CE marking CE conform EN 15964, NHTSA, FDA Conformity, depending on configuration Integrated clock		specific
Sampling Automatic sampling when minimum volume resp. blow time is reached; Automatic sampling when end of breath is reached; depending on configuration  Ready for use Approx. 4 seconds after switching on  Display of the measurement results After approx. 3 s (at 0.00 %); After approx. 3 s (at 0.00 %); After approx. 10 s (at 1.00 %, room temperature)  Operating temperature -5 to +50 °C / 23 to 122 °F  Relative humidity 10 to 100 % relative humidity (non-condensing and in operating state)  Ambient pressure 600 to 1,300 hPa / 17.7 to 38.4 inch Hg  Display Graphic backlit LCD display; 32 x 22 mm / 1.3" x 0.9" (128 x 64 pixels)  LED Blue light emitting diode (LED) to support the indication of results and warning message  Audible signal Various acoustic signals to support messages and warnings on the display  Datalogger Memory of last 400 tests  Power supply Replaceable CR123A-Battery (1,pcs), charge level indicator in display, with one battery up to. 1,500 breath tests can be done.  Mouthpiece Hygienically and individually packed  Operating concept Measurement functions can be performed using just one button  Wet gas or dry gas calibration  Housing Impact resistant ABS/PC  Dimensions (W x H x D), weight Approx. 50 x 133 x 29 mm / approx. 120 g, incl. Battery  Wibration Albook EN 6068-2-32  CE marking CE conform  Norms EN 15964, NHTSA, FDA Conformity, depending on configuration  Integrated clock	Measuring range	0 to 5.00 %; if the limits of the measuring range are exceeded,
reached; Automatic sampling when end of breath is reached; depending on configuration  Ready for use Approx. 4 seconds after switching on After approx. 3 s (at 0.00 %); After approx. 10 s (at 1.00 %, room temperature)  Operating temperature -5 to -50 °C / 23 to 122 °F Relative humidity 10 to 100 % relative humidity (non-condensing and in operating state)  Ambient pressure 600 to 1,300 hPa / 17.7 to 38.4 inch Hg Display Graphic backlit LCD display; 32 x 22 mm / 1.3° x 0.9° (128 x 64 pixels)  LED Blue light emitting diode (LED) to support the indication of results and warning message Audible signal  Various acoustic signals to support messages and warnings on the display  Datalogger Memory of last 400 tests  Power supply Replaceable CR123A-Battery (1.pcs), charge level indicator in display, with one battery up to 1,500 breath tests can be done.  Mouthpiece Hygienically and individually packed Operating concept Measurement functions can be performed using just one button Calibration Wet gas or dry gas calibration Housing Impact resistant ABS/PC Dimensions (W x H x D), weight Approx. 50 x 133 x 29 mm / approx. 120 g, incl. Battery Vibration and shock EN 60068-2-32 CE conform Norms EN 15964, NHTSA, FDA Conformity, depending on configuration Integrated clock To show the last service date		a message is displayed
Ready for use     Automatic sampling when end of breath is reached; depending on configuration       Display of the measurement results     Approx. 4 seconds after switching on       After approx. 10 s (at 1.00 %o, room temperature)     After approx. 10 s (at 1.00 %o, room temperature)       Operating temperature     -5 to +50 °C / 23 to 122 °F       Relative humidity     10 to 100 % relative humidity (non-condensing and in operating state)       Ambient pressure     600 to 1,300 hPa / 17.7 to 38.4 inch Hg       Display     Graphic backlit LCD display; 32 x 22 mm / 1.3° x 0.9° (128 x 64 pixels)       LED     Blue light emitting diode (LED) to support the indication of results and warning message       Audible signal     Various acoustic signals to support messages and warnings on the display       Datalogger     Memory of last 400 tests       Power supply     Replaceable CR123A-Battery (1.pcs), charge level indicator in display, with one battery up to. 1,500 breath tests can be done.       Mouthpiece     Hygienically and individually packed       Operating concept     Measurement functions can be performed using just one button       Calibration     Wet gas or dry gas calibration       Housing     Impact resistant ABS/PC       Dimensions (W x H x D), weight     Approx. 50 x 133 x 29 mm / approx. 120 g, incl. Battery       Vibration and shock     EN 60068-2-32       CE marking     CE conform       Norms     EN 6068-2-32	Sampling	Automatic sampling when minimum volume resp. blow time is
Ready for use       Approx. 4 seconds after switching on         Display of the measurement results       After approx. 3 s (at 0.00 %);         After approx. 10 s (at 1.00 %, room temperature)         Operating temperature       -5 to +50 °C / 23 to 122 °F         Relative humidity       10 to 100 % relative humidity (non-condensing and in operating state)         Ambient pressure       600 to 1,300 hPa / 17.7 to 38.4 inch Hg         Display       Graphic backlit LCD display;         32 x 22 mm / 1.3° x 0.9° (128 x 64 pixels)         LED       Blue light emitting diode (LED) to support the indication of results and warning message         Audible signal       Various acoustic signals to support messages and warnings on the display         Datalogger       Memory of last 400 tests         Power supply       Replaceable CR123A-Battery (1,pcs), charge level indicator in display, with one battery up to .1,500 breath tests can be done.         Mouthpiece       Hygienically and individually packed         Operating concept       Measurement functions can be performed using just one button         Calibration       Wet gas or dry gas calibration         Housing       Impact resistant ABS/PC         Dimensions (W x H x D), weight       Approx. 50 x 133 x 29 mm / approx. 120 g, incl. Battery         Vibration and shock       EN 60068-23         CE marking       CE conform		reached;
Ready for use Display of the measurement results After approx. 3 s (at 0.00 %); After approx. 10 s (at 1.00 %, room temperature) Operating temperature -5 to +50 °C / 23 to 122 °F Relative humidity 10 to 100 % relative humidity (non-condensing and in operating state) Ambient pressure 600 to 1,300 hPa / 17.7 to 38.4 inch Hg Display Graphic backlit LCD display; 32 x 22 mm / 1.3" x 0.9" (128 x 64 pixels)  ELD Blue light emitting diode (LED) to support the indication of results and warning message Audible signal Various acoustic signals to support messages and warnings on the display  Datalogger Memory of last 400 tests Power supply Replaceable CR123A-Battery (1.pcs), charge level indicator in display, with one battery up to 1.1,500 breath tests can be done.  Mouthpiece Hygienically and individually packed Operating concept Measurement functions can be performed using just one button Wet gas or dry gas calibration Housing Impact resistant ABS/PC Dimensions (W x H x D), weight Vibration and shock EN 60068-2-32 CE marking Norms EN 15964, NHTSA, FDA Conformity, depending on configuration Integrated clock To show the last service date		Automatic sampling when end of breath is reached;
Display of the measurement results  After approx. 3 s (at 0.00 %); After approx. 10 s (at 1.00 %, room temperature)  -5 to +50 °C / 23 to 122 °F  Relative humidity  10 to 100 % relative humidity  (non-condensing and in operating state)  Ambient pressure  600 to 1,300 hPa / 17.7 to 38.4 inch Hg  Display  Graphic backlit LCD display; 32 x 22 mm / 1.3° x 0.9° (128 x 64 pixels)  Blue light emitting diode (LED) to support the indication of results and warning message  Audible signal  Various acoustic signals to support messages and warnings on the display  Memory of last 400 tests  Power supply  Replaceable CR123A-Battery (1.pcs), charge level indicator in display, with one battery up to 1.500 breath tests can be done.  Mouthpiece  Hygienically and individually packed  Operating concept  Measurement functions can be performed using just one button  Calibration  Housing  Impact resistant ABS/PC  Dimensions (W x H x D), weight  Approx. 50 x 133 x 29 mm / approx. 120 g, incl. Battery  Vibration and shock  EN 60068-2-32  CE marking  Norms  EN 15964, NHTSA, FDA Conformity, depending on configuration  Integrated clock  To show the last service date		depending on configuration
After approx. 10 s (at 1.00 ‰, room temperature)  Operating temperature  -5 to +50 °C / 23 to 122 °F  Relative humidity  10 to 100 % relative humidity  (non-condensing and in operating state)  600 to 1,300 hPa / 17.7 to 38.4 inch Hg  Display  Graphic backlit LCD display; 32 x 22 mm / 1.3" x 0.9" (128 x 64 pixels)  LED  Blue light emitting diode (LED) to support the indication of results and warning message  Audible signal  Various acoustic signals to support messages and warnings on the display  Memory of last 400 tests  Power supply  Replaceable CR123A-Battery (1.pcs), charge level indicator in display, with one battery up to 1,500 breath tests can be done.  Mouthpiece  Hygienically and individually packed  Operating concept  Measurement functions can be performed using just one button  Calibration  Housing  Impact resistant ABS/PC  Dimensions (W x H x D), weight  Approx. 50 x 133 x 29 mm / approx. 120 g, incl. Battery  Vibration and shock  EN 60068-2-32  CE marking  Norms  EN 15964, NHTSA, FDA Conformity, depending on configuration  Integrated clock  To show the last service date	Ready for use	Approx. 4 seconds after switching on
Operating temperature       -5 to +50 °C / 23 to 122 °F         Relative humidity       10 to 100 % relative humidity (non-condensing and in operating state)         Ambient pressure       600 to 1,300 hPa / 17.7 to 38.4 inch Hg         Display       Graphic backlit LCD display; 32 x 22 mm / 1.3" x 0.9" (128 x 64 pixels)         LED       Blue light emitting diode (LED) to support the indication of results and warning message         Audible signal       Various acoustic signals to support messages and warnings on the display         Datalogger       Memory of last 400 tests         Power supply       Replaceable CR123A-Battery (1.pcs), charge level indicator in display, with one battery up to. 1,500 breath tests can be done.         Mouthpiece       Hygienically and individually packed         Operating concept       Measurement functions can be performed using just one button         Calibration       Wet gas or dry gas calibration         Housing       Impact resistant ABS/PC         Dimensions (W x H x D), weight       Approx. 50 x 133 x 29 mm / approx. 120 g, incl. Battery         Vibration and shock       EN 60068-2-32         CE marking       CE conform         Norms       EN 15964, NHTSA, FDA Conformity, depending on configuration         Integrated clock       To show the last service date	Display of the measurement results	After approx. 3 s (at 0.00 ‰);
Relative humidity  10 to 100 % relative humidity (non-condensing and in operating state)  600 to 1,300 hPa / 17.7 to 38.4 inch Hg Display  Graphic backlit LCD display; 32 x 22 mm / 1.3" x 0.9" (128 x 64 pixels)  LED  Blue light emitting diode (LED) to support the indication of results and warning message  Audible signal  Various acoustic signals to support messages and warnings on the display  Datalogger  Memory of last 400 tests  Replaceable CR123A-Battery (1.pcs), charge level indicator in display, with one battery up to. 1,500 breath tests can be done.  Mouthpiece  Hygienically and individually packed  Operating concept  Measurement functions can be performed using just one button  Wet gas or dry gas calibration  Housing  Impact resistant ABS/PC  Dimensions (W x H x D), weight  Vibration and shock  EN 60068-2-32  CE marking  CE conform  Norms  EN 15964, NHTSA, FDA Conformity, depending on configuration  Integrated clock  To show the last service date		After approx. 10 s (at 1.00 ‰, room temperature)
Ambient pressure  600 to 1,300 hPa / 17.7 to 38.4 inch Hg  Display  Graphic backlit LCD display; 32 x 22 mm / 1.3" x 0.9" (128 x 64 pixels)  LED  Blue light emitting diode (LED) to support the indication of results and warning message  Audible signal  Various acoustic signals to support messages and warnings on the display  Datalogger  Memory of last 400 tests  Power supply  Replaceable CR123A-Battery (1.pcs), charge level indicator in display, with one battery up to. 1,500 breath tests can be done.  Mouthpiece  Hygienically and individually packed  Operating concept  Measurement functions can be performed using just one button  Wet gas or dry gas calibration  Housing  Impact resistant ABS/PC  Dimensions (W x H x D), weight  Vibration and shock  EN 60068-2-32  CE marking  Norms  EN 15964, NHTSA, FDA Conformity, depending on configuration  Integrated clock  To show the last service date	Operating temperature	-5 to +50 °C / 23 to 122 °F
Ambient pressure       600 to 1,300 hPa / 17.7 to 38.4 inch Hg         Display       Graphic backlit LCD display;         32 x 22 mm / 1.3" x 0.9" (128 x 64 pixels)         LED       Blue light emitting diode (LED) to support the indication of results and warning message         Audible signal       Various acoustic signals to support messages and warnings on the display         Datalogger       Memory of last 400 tests         Power supply       Replaceable CR123A-Battery (1.pcs), charge level indicator in display, with one battery up to .1,500 breath tests can be done.         Mouthpiece       Hygienically and individually packed         Operating concept       Measurement functions can be performed using just one button         Calibration       Wet gas or dry gas calibration         Housing       Impact resistant ABS/PC         Dimensions (W x H x D), weight       Approx. 50 x 133 x 29 mm / approx. 120 g, incl. Battery         Vibration and shock       EN 60068-2-32         CE marking       CE conform         Norms       EN 15964, NHTSA, FDA Conformity, depending on configuration         Integrated clock       To show the last service date	Relative humidity	10 to 100 % relative humidity
Display       Graphic backlit LCD display;         32 x 22 mm / 1.3" x 0.9" (128 x 64 pixels)         Blue light emitting diode (LED) to support the indication of results and warning message         Audible signal       Various acoustic signals to support messages and warnings on the display         Datalogger       Memory of last 400 tests         Power supply       Replaceable CR123A-Battery (1.pcs), charge level indicator in display, with one battery up to. 1,500 breath tests can be done.         Mouthpiece       Hygienically and individually packed         Operating concept       Measurement functions can be performed using just one button         Calibration       Wet gas or dry gas calibration         Housing       Impact resistant ABS/PC         Dimensions (W x H x D), weight       Approx. 50 x 133 x 29 mm / approx. 120 g, incl. Battery         Vibration and shock       EN 60068-2-32         CE marking       CE conform         Norms       EN 15964, NHTSA, FDA Conformity, depending on configuration         Integrated clock       To show the last service date		(non-condensing and in operating state)
Blue light emitting diode (LED) to support the indication of results and warning message  Audible signal  Audible signal  Datalogger  Description  Memory of last 400 tests  Power supply  Replaceable CR123A-Battery (1.pcs), charge level indicator in display, with one battery up to. 1,500 breath tests can be done.  Mouthpiece  Hygienically and individually packed  Operating concept  Measurement functions can be performed using just one button  Wet gas or dry gas calibration  Housing  Impact resistant ABS/PC  Dimensions (W x H x D), weight  Approx. 50 x 133 x 29 mm / approx. 120 g, incl. Battery  Vibration and shock  EN 60068-2-32  CE marking  OE conform  Norms  EN 15964, NHTSA, FDA Conformity, depending on configuration  Integrated clock	Ambient pressure	600 to 1,300 hPa / 17.7 to 38.4 inch Hg
Blue light emitting diode (LED) to support the indication of results and warning message  Audible signal  Various acoustic signals to support messages and warnings on the display  Datalogger  Memory of last 400 tests  Replaceable CR123A-Battery (1.pcs), charge level indicator in display, with one battery up to. 1,500 breath tests can be done.  Mouthpiece  Hygienically and individually packed  Operating concept  Measurement functions can be performed using just one button  Wet gas or dry gas calibration  Housing  Impact resistant ABS/PC  Dimensions (W x H x D), weight  Vibration and shock  EN 60068-2-32  CE marking  Norms  EN 15964, NHTSA, FDA Conformity, depending on configuration  Integrated clock	Display	Graphic backlit LCD display;
Audible signal  Audible signal  Postalogger  Power supply  Replaceable CR123A-Battery (1.pcs), charge level indicator in display, with one battery up to. 1,500 breath tests can be done.  Mouthpiece  Hygienically and individually packed  Operating concept  Measurement functions can be performed using just one button  Calibration  Housing  Impact resistant ABS/PC  Dimensions (W x H x D), weight  Vibration and shock  EN 60068-2-32  CE conform  Norms  EN 15964, NHTSA, FDA Conformity, depending on configuration  Integrated clock  To show the last service date		32 x 22 mm / 1.3" x 0.9" (128 x 64 pixels)
Audible signal  Various acoustic signals to support messages and warnings on the display  Datalogger  Power supply  Replaceable CR123A-Battery (1.pcs), charge level indicator in display, with one battery up to. 1,500 breath tests can be done.  Mouthpiece  Hygienically and individually packed  Operating concept  Measurement functions can be performed using just one button  Calibration  Wet gas or dry gas calibration  Housing  Impact resistant ABS/PC  Dimensions (W x H x D), weight  Vibration and shock  EN 60068-2-32  CE conform  Norms  EN 15964, NHTSA, FDA Conformity, depending on configuration  Integrated clock  To show the last service date	LED	Blue light emitting diode (LED) to support the indication of results
the display  Datalogger  Memory of last 400 tests  Replaceable CR123A-Battery (1.pcs), charge level indicator in display, with one battery up to. 1,500 breath tests can be done.  Mouthpiece  Hygienically and individually packed  Operating concept  Measurement functions can be performed using just one button  Calibration  Wet gas or dry gas calibration  Housing  Impact resistant ABS/PC  Dimensions (W x H x D), weight  Vibration and shock  EN 60068-2-32  CE marking  CE conform  Norms  EN 15964, NHTSA, FDA Conformity, depending on configuration  Integrated clock  To show the last service date		and warning message
Datalogger  Power supply  Replaceable CR123A-Battery (1.pcs), charge level indicator in display, with one battery up to 1,500 breath tests can be done.  Mouthpiece  Hygienically and individually packed  Operating concept  Measurement functions can be performed using just one button  Wet gas or dry gas calibration  Housing  Impact resistant ABS/PC  Dimensions (W x H x D), weight  Vibration and shock  EN 60068-2-32  CE marking  CE conform  Norms  EN 15964, NHTSA, FDA Conformity, depending on configuration  Integrated clock  To show the last service date	Audible signal	Various acoustic signals to support messages and warnings on
Power supply  Replaceable CR123A-Battery (1.pcs), charge level indicator in display, with one battery up to. 1,500 breath tests can be done.  Mouthpiece Hygienically and individually packed  Operating concept Measurement functions can be performed using just one button  Calibration Wet gas or dry gas calibration  Housing Impact resistant ABS/PC  Dimensions (W x H x D), weight Approx. 50 x 133 x 29 mm / approx. 120 g, incl. Battery  Vibration and shock EN 60068-2-32  CE marking CE conform  Norms EN 15964, NHTSA, FDA Conformity, depending on configuration  Integrated clock To show the last service date		the display
display, with one battery up to. 1,500 breath tests can be done.  Mouthpiece Hygienically and individually packed Operating concept Measurement functions can be performed using just one button Calibration Wet gas or dry gas calibration Housing Impact resistant ABS/PC Dimensions (W x H x D), weight Approx. 50 x 133 x 29 mm / approx. 120 g, incl. Battery Vibration and shock EN 60068-2-32 CE marking CE conform Norms EN 15964, NHTSA, FDA Conformity, depending on configuration Integrated clock To show the last service date	Datalogger	Memory of last 400 tests
Mouthpiece  Operating concept  Measurement functions can be performed using just one button  Wet gas or dry gas calibration  Housing  Impact resistant ABS/PC  Dimensions (W x H x D), weight  Vibration and shock  EN 60068-2-32  CE marking  Norms  EN 15964, NHTSA, FDA Conformity, depending on configuration  Integrated clock  Hygienically and individually packed  Measurement functions can be performed using just one button  Wet gas or dry gas calibration  Impact resistant ABS/PC  Approx. 50 x 133 x 29 mm / approx. 120 g, incl. Battery  EN 60068-2-32  CE conform  EN 15964, NHTSA, FDA Conformity, depending on configuration  To show the last service date	Power supply	Replaceable CR123A-Battery (1.pcs), charge level indicator in
Operating concept  Measurement functions can be performed using just one button  Wet gas or dry gas calibration  Housing  Impact resistant ABS/PC  Dimensions (W x H x D), weight  Vibration and shock  EN 60068-2-32  CE marking  Norms  EN 15964, NHTSA, FDA Conformity, depending on configuration  Integrated clock  Measurement functions can be performed using just one button  Wet gas or dry gas calibration  Impact resistant ABS/PC  Approx. 50 x 133 x 29 mm / approx. 120 g, incl. Battery  EN 60068-2-32  CE conform  EN 15964, NHTSA, FDA Conformity, depending on configuration  To show the last service date		display, with one battery up to. 1,500 breath tests can be done.
Calibration  Wet gas or dry gas calibration  Housing  Impact resistant ABS/PC  Approx. 50 x 133 x 29 mm / approx. 120 g, incl. Battery  Vibration and shock  EN 60068-2-32  CE marking  CE conform  EN 15964, NHTSA, FDA Conformity, depending on configuration  Integrated clock  To show the last service date	Mouthpiece	Hygienically and individually packed
Housing Impact resistant ABS/PC  Dimensions (W x H x D), weight Approx. 50 x 133 x 29 mm / approx. 120 g, incl. Battery  Vibration and shock EN 60068-2-32  CE marking CE conform  Norms EN 15964, NHTSA, FDA Conformity, depending on configuration  Integrated clock To show the last service date	Operating concept	Measurement functions can be performed using just one button
Dimensions (W x H x D), weight  Approx. 50 x 133 x 29 mm / approx. 120 g, incl. Battery  Vibration and shock  EN 60068-2-32  CE conform  Norms  EN 15964, NHTSA, FDA Conformity, depending on configuration  Integrated clock  To show the last service date	Calibration	Wet gas or dry gas calibration
Vibration and shock  EN 60068-2-32  CE marking  CE conform  EN 15964, NHTSA, FDA Conformity, depending on configuration  Integrated clock  EN 60068-2-32  To show the last service date	Housing	Impact resistant ABS/PC
CE marking  Norms  EN 15964, NHTSA, FDA Conformity, depending on configuration  Integrated clock  CE conform  EN 15964, NHTSA, FDA Conformity, To show the last service date	Dimensions (W x H x D), weight	Approx. 50 x 133 x 29 mm / approx. 120 g, incl. Battery
Norms  EN 15964, NHTSA, FDA Conformity, depending on configuration Integrated clock  To show the last service date	Vibration and shock	EN 60068-2-32
Integrated clock     depending on configuration       To show the last service date	CE marking	CE conform
Integrated clock To show the last service date	Norms	EN 15964, NHTSA, FDA Conformity,
		depending on configuration
IP protection class IP52	Integrated clock	To show the last service date
	IP protection class	IP52

# Ordering Information

Dräger Alcotest® 4000 - Standard (pre-configured)	37 06 317
Dräger Alcotest® 4000 – Configurator	37 06 319
Dräger Alcotest® 4000 – Nordics	37 06 953
Dräger Alcotest® 4000 – USA	37 06 325
Dräger Alcotest® 4000 – Australien	37 06 951
Dräger A4000 additional 5 mouthpieces, hygienically and	83 25 250
individually packed	
Microfibre bag	83 24 994

#### Notes



Not all products, features, or services are for sale in all countries. Mentioned Trademarks are only registered in certain countries and not necessarily in the country in which this material is released. Go to www.draeger.com/trademarks to find the current status.

#### CORPORATE HEADQUARTERS

Drägerwerk AG & Co. KGaA Moislinger Allee 53–55 23558 Lübeck, Germany www.draeger.com

#### REGION EUROPE

Dräger Safety AG & Co. KGaA Revalstraße 1 23560 Lübeck, Germany Tel +49 451 882 0 Fax +49 451 882 2080 info@draeger.com

#### REGION MIDDLE EAST, AFRICA

Dräger Safety AG & Co. KGaA Branch Office P.O. Box 505108 Dubai, United Arab Emirates Tel +971 4 4294 600 Fax +971 4 4294 699 contactuae@draeger.com

#### **REGION ASIA PACIFIC**

Draeger Singapore Pte. Ltd. 61 Science Park Road The Galen #04-01 Singapore 117525 Tel: +65 6872 9288 Fax: +65 6259 0398 asia.pacific@draeger.com

# REGION CENTRAL AND SOUTH AMERICA

Dräger Indústria e Comércio Ltda. Al. Pucurui - 51 - Tamboré 06406-100 - Barueri - SP Tel. +55 (11) 4689-4900 relacionamento@draeger.com

Locate your Regional Sales Representative at: www.draeger.com/contact

